



GROUT TRANSFORMER-QUICK-SET GROUT WATER SOLIDIFIER

PRODUCT DATA SHEET

623 Chatsworth Hwy 225

Calhoun, GA 30701

706.403.3286

lamininindustries.com

Grout Transformer is a proprietary polymer blend used to quickly transform liquid grout water into an EPA-approved, landfill-accepted solid that keeps damaging grout water out of drains.



Features and Benefits

- Fast and easy way to solidify leftover grout/ grout water into a disposable solid
- Eliminates call backs and repairs due to improper disposal of grout water down drains
- Meets all EPA requirements for disposal of liquid waste into landfills
- Protects from environmental fines
- Passes paint filter test (for aqueous solutions)
- Passes toxicity characteristic leaching procedure test (TCLP) for heavy metals
- Traps high pH water and silicates without releasing them back to the environment
- Non-leaching

Testing

Grout Transformer has passed the following tests:

- EPA Test 9095, commonly called the Paint Filer Test. Passing this test means the solidified material is suitable for placement into the local landfill because there are no free liquids present
- Toxicity Characteristics Leaching Procedure Test (TCLP). Passing this test means Grout Transformer does not exceed strict standards for the presence of organic and inorganic analytes

Directions

- Add 1 4oz cup of Grout Transformer per gallon quantity of grout water or 1 pint (16 oz) of Grout Transformer per 5 gallon bucket of Grout water
- Grout Transformer should be thoroughly mixed with the grout water and left to absorb the water. If the mixture is still too fluid, additional Grout Transformer should be added until a desired consistency is achieved
- Ensure proper disposal based on your approved on-site specific waste plan

Technical Information

- Product Characteristics Formulation Particle Type pH (1% dispersion)
- Dehydrator Semi -Granular 6.5 – 8.5
- Dehydrator SF Semi-Granular 5.5 – 6.5

Available size: 1 Gallon Pail, 4 Gallon Pail