





CRETECLEAN PLUS AUTO SCRUBBER™

MAINTENANCE GUIDE

623 Chatsworth Hwy 225

Calhoun, GA 30701

706.403.3286

lamininindustries.com



Sweep and remove large debris and trash from the floor. Pay special attention to entrance doors and floor edges where dirt and dust are most likely to collect.

Dip the scrub brush into the cleaning solution and scrub soiled and high traffic areas thoroughly. Pay special attention to entrances, furniture bases, and areas prone to spills and soil.

Fill the tank with fresh water and add CreteClean Plus. Do not add the cleaner before the water. This could result in unnecessary foaming.







Auto scrub the floor according to the equipment manufacturer's recommendations. As a general rule, an auto scrubber will clean approximately 500-1000 ft² per gallon of cleaning solution.

Use a squeegee to pull any residual cleaning liquid away from the wall edges towards the center of the room.

When finished, pick up the remaining liquid with the auto scrubber.



Do not allow spills to dwell on the floor. Display "Wet Floor" sign and clean immediately with a damp mop.

Spray the affected area generously with CreteClean Plus cleaning solution to lift any remaining contaminants out of the concrete pores. Mop the area a second time, ensuring that the cleaning solution and contaminants have been removed completely. Allow the floor to dry.

